



No.	Name	Note	No.	Name	Note
1	Angle valve	1/4"Flare	16	Angle valve	1/4"Flare
2	Discharge flange	2 1/2"	17	Rear front service valve	1/4"Flare
3	Solenoid valve	50%(NC)	18	Solenoid valve	Separative or NO, option
4	Solenoid valve	75%(NC)	19	Liquid injection connector	5/8"Flare, option
5	Solenoid valve	25%(NC)	20	Suction flange	4"
6	Liquid/oil or refrigerant injection connector	3/8"Flare, option	21	Cable box	Standard
7	Capillary		22	Service flange	
8	Check valve	2 1/2"	23	Oil drain valve	option
9	Oil sight glass	Low side	24	Oil level switch	option
10	Oil heater	150W/300W	25	Discharge Temp. sensor	110°C
11	Oil filter cartridge		26	Safety Valve	1"NP1,option
12	Oil pressure differential switch	Connector, option	27	Economizer port	7/8", solder
13	Oil connector(out)	5/8"Flare, option	28	Oil sight glass	High side
14	Stop pin	option	29	Over flow port	option
15	Oil connector(in)	5/8"Flare, option			

\*All stop valves are optional

UNIT  
SI: mm Imperial: (in)

6	2014.08.21	Dimension correction
5	2012.11.06	Dimension correction
4	2012.04.16	Delete 1.Connector 2.Oil temp. sensor
Item	Date	Modification

Model	RC2-470A
Name	Compressor outline
	<b>JR HANBELL</b> Ver. 06