



MCS-ETHERNET-SWITCH-NO-PS

Description & Specifications



Part # **MCS-ETHERNET-SWITCH-NO-PS**

Description

The **MCS-ETHERNET-SWITCH** is a compact, fast industrial Ethernet switch equipped with five 10/100Base-TX ports. By using standard auto-negotiation and the inclusion of auto-MDIX, the MCS-ETHERNET-SWITCH delivers a cost-effective way of integrating legacy 10 Mbps networks with 100 Mbps fast Ethernet networks.

The MCS-ETHERNET-SWITCH series switch can be DIN-rail mounted and is equipped with a removable power input terminal block to accommodate just about any application that requires an Ethernet switch.

KIT INCLUDES-

MCS-Ethernet-Switch and
MCS-Ethernet-Switch Mounting Kit,
7ft CAT 5e Patch Cord, Blue



Specifications

Ethernet Switch

Serial Interface	5-port 10/100 Base-TX
Address Table Size	2048 MAC addresses
Network Interface	10/100 Mbps full/half-duplex, auto negotiation, auto MDI/MDXI
LED Indicators	Power Status, Link/Activity (Green), Speed (Yellow)
Power	Input Voltage: 10 to 36 VDC Input Voltage: 8 to 24 VAC
Dimensions	25mm W x 70mm D x 116mm H (1.00" W x 2.74" D x 4.53" H)
Mounting	TS-35 DIN Rail Mount
Input Frequency	47 Hz to 63 Hz
Output Voltage	12 VDC
Over Voltage	14.2-16.2V
Protection type	Shut down o/p voltage, power on to recover
Voltage Tolerance	±2.0%
Working Temperature	-22~158°F - (30~+70°C)
Efficiency	88 %
Type	Auto Switching
Agency Approvals	UL508/CUL/TUV/CE/CB

Packaging

Ship Weight	2.0 lb (approx)
Box Dimensions	6" x 6" x 6"(approx)

Revision 2021-07-06