



MAGNUM-TOUCH-15.4-KP-DEMO-12

Description & Specifications



MAGNUM-TOUCH-15.4-KP-DEMO-12

Description

The **MCS-TOUCH-15.4-KP-DEMO-12** consists of a Magnum micro controller, **MCS-RO-BASE**, **MCS-RO-EXT**, **MCS-SI-BASE**, **MCS-SI-EXT** expansion boards and a MCS-TOUCH-15.4 capacitive touchscreen interface.

Also installed in the Demo unit is a **MCS-EXV DRIVER**, **MCS-500 Transducer** with cable, **MCS-KEYPAD-PANL-12**, **MCS-CT300**, a **MCS-POCKET ROUTER** and a **MCS-T100**. This setup allows the user to test both the demo unit and various software configurations in-house.

Communication with these units occurs at 38,400 baud over the MCS-I/O port, which is dedicated to this purpose.

MCS-CONFIG and **MCS-CONNECT** software packages are installed allowing for system configuration, dynamic on-line display screens, remote communication, graphing and more.

The MCS-MAGNUM is a durable microprocessor based controller designed for the hostile environment of the HVAC/R industry. It is designed to be the primary manager of the package it is controlling.

The MCS-MAGNUM provides flexibility with setpoints and control options that are selectable prior to commissioning a system or when the unit is live. Displays, alarms and other interfaces are accomplished in a clear and simple language that informs the user as to the status of the controller.

An Ethernet and RS-485 port is also provided for communication with other manufacturers systems.

MCS-MAGNUM has built-in support for Modbus RTU, MCS IP and MCS 485.

Demo Box Specifications

Dimensions..... 16" w x 21" h x 8" d

Temp. Range for Enclosure/Touchscreen

Operating Temperature..... -32°F to +158°F (-0°C to +70°C)
Operating Humidity..... 0-95% Non-Condensing
Storage Temperature..... -4°F to +158°F (-20°C to +70°C)

Controller Specification

Microprocessor Zilog eZ80 Acclaim! @ 50mhz
Sensor Inputs (SI)..... 12 inputs 0-5vdc (10-bit Analog or Digital)
Digital Inputs..... 4 inputs 0 or 5vdc only
Relay Outputs (RO)..... 10 outputs 6.3amps @ 230vac
Analog Outputs (AO)..... 4 outputs 0-10vdc
Printed Circuit Board Six layer with separate power & ground planes
Input Power (Standard)..... +12vdc at 0.7amps (fully loaded)
MCS-I/O Comm Port 1 @ 38,400 baud
RS-485 Comm Port 1 @ 19,200 baud
Ethernet..... 10/100 Mbps Ethernet
Real Time Clock Battery backup
Power Detection Automatic power fail reset

MCS-SI-BASE and MCS-SI-EXT Expansion Boards

Sensor Inputs (SI)..... 32 inputs 0-5vdc (10-bit A/D)
Analog Outputs (AO) 8 outputs 0-10vdc
MCS-I/O Comm Port 1 @ 38,400 baud

MCS-RO-BASE and MCS-RO-EXT Expansion Boards

Relay Outputs (RO)..... 20 outputs 5amps @ 230VAC

MCS-TOUCH-15.4 - Capacitive Touchscreen

Dimensions..... 17"L x 12.11"W x 3.228"H
Gasket BISCO HT-820-Firm Cellular Silicone
LCD Screen..... 15.4" (16:10 Diagonal) 16.2 Million Colors
1280x800 Resolution
Soft Touch Capacitive Stylus pen
Power Input 12Vdc 2 amps
Motherboard Freescale i.MX6 Dual Core 800mhz
1Gb of 512mhz DDR3 RAM Mem.
4Gb of eMMC Flash memory
1Gb Ethernet (100Mb/10Mb comp.)
1 Micro-SD Slots;
2 USB Host 2.0; Real Time Clock (RTC)
w/ Battery

Kit Content

Pelican carrying case, Keyboard with USB connector, removable stylus touch pen, MCS-500-Transducer and cable.

