



# MCS-MAGNUM-NEMA4-15.4-12

## Description & Specifications



Part # MCS-MAGNUM-NEMA4-15.4-12

### Description

The MCS-MAGNUM-NEMA4-15.4-12 is a **custom built enclosure** made of powder coated aluminum for durability and longevity. It is a NEMA TYPE 4 rating. The interior left hand swing door is mounted with three four-inch hinges for strength. The enclosure is designed for areas which may be regularly hosed down or are in very wet or oily conditions. The enclosure provides protection from dust, dirt, oil and water.

**Standard MCS-MAGNUM-NEMA4-15.4-12 Enclosure** - includes a MCS-MAGNUM-N-12, a touchscreen 15.4" display, a MCS-SI-BASE, 20 amp circuit breaker, electrical outlet for plug-in power at the box, industrial 5 port Ethernet switch, 12vdc power supply, 5 amp circuit breaker and Terminal blocks.

The MCS-TOUCH-15.4 capacitive touchscreen interface designed to simplify user access with the MCS-Magnum and MicroMag utilizing MCS-Connect to provide both graphics and service mode access to technicians. Input method: Finger, Stylus or \*Glove.

Highly accurate and does not require calibration - easy to clean glass surface. Works outdoors, bright screen, water resistant, exceptional Optics - 1280x800 resolution, sharp and vibrant images.

MCS-TOUCH-15.4 comes preloaded with the MCS-CONNECT program that allows you to view the 'unit's status', 'extended history', 'alerts', 'alarms', setpoints, and more, all in a user-friendly graphic format. The MCS-TOUCH-15.4-12 can connect up to 60 MCS controllers and supports RS485 or Ethernet networking.

Communication to these units occur at 38,400 baud over the MCS-I/O port which is dedicated for this purpose.

SHIELDWIRE-GROUNDING multi-terminal connectors are included to eliminate stray electrical current, thereby helping to reduce line noise form the sensors to the controller.

### Specifications

#### NEMA Rating – Type 4 Enclosure

#### Industrial Control Panel

- Dimensions of control panel .36"H x 30"W x 12"D
- Mounting Holes..... Mounts with four pre-drilled 15/32" holes
- Rated Voltage (Standard) ..... 120VAC or 230VAC
- Phase / Frequency ..... 1 Phase / 60Hz
- Full Load Current(approx) .... 40A at 120VAC or 20A at 240VAC
- Short Circuit Current Rating . 10kA
- Dimensions of control panel .27"w x 34.75"h x 8.0"d
- Mounting Holes..... Mounts with four pre-drilled 15/32" holes

#### Temp. Range for Control Panel & Touch Screen

- Operating Temperature..... -4°F to 158°F (-20°C to 70°C)
- Operating Humidity..... 0-95% Non-Condensing
- Storage Temperature..... -4°F to 158°F (-20°C to 70°C)

#### MCS-MAGNUM Specification

- Microprocessor .....Zilog eZ80 Acclaim! @ 50mhz
- Sensor Inputs (SI)..... 12 inputs 0-5vdc (10-bit A/D)
- Digital Inputs..... 4 inputs 0 or 5vdc only
- Relay Outputs (RO)..... 10 outputs 6.3amps @ 230vac
- Analog Outputs (AO) ..... 4 outputs 0-10vdc
- Printed Circuit Board ..... Six layer with separate power and ground planes
- Input Power (Standard) ..... 12 vdc Regulated Power Supply
- Minimum (Brown in) ..... 9.44 vdc
- Amp Draw (Loaded) ..... 857.0 mA
- RS-485 Comm Port ..... 1 @ 19,200 baud
- Ethernet ..... 10/100 Mbps Ethernet
- Real Time Clock ..... Battery backup
- Power Detection ..... Automatic power fail reset

#### MCS-SI-BASE/EXT Expansion Board

- Sensor Inputs (SI)..... 48 inputs 0-5vdc (2 Base/1Ext)
- Analog Outputs (AO) ..... 12 outputs 0-10vdc
- MCS-I/O Comm Port ..... 1 @ 38,400 baud

#### MCS-TOUCH-15.4 - Capacitive Touchscreen

- Dimensions..... 17"L x 12.11"W x 3.228"H
- LCD Screen ..... 15.4" (16:10 Diagonal)
- Gasket..... BISCO HT-820-Firm Cellular Silicone
- 16.2 Million Colors
- 1280x800 Resolution
- Soft Touch Capacitive Stylus pen
- Power Input ..... 12Vdc 2 amps
- Touchscreen Surface..... UV Degradation Protection

#### Packaging

- Weight ..... 90 lbs(approx)
- Box ..... 29" x 10" x 37"

5580 Enterprise Pkwy., Fort Myers, FL 33905

Office: 239-694-0089 • Fax: 239-694-0031 [www.mcscontrols.com](http://www.mcscontrols.com)

\* The glove needs to have a conductive fabric or material to work with cap touchscreens.