



MCS-REMOTE-10.1

Description & Specifications



Part #
MCS-REMOTE-MLB-10.1

Description

The **MCS-REMOTE-10.1** enclosure is made of powder coated aluminum for durability and longevity. A left hand swing door is mounted with three four-inch hinges for strength. A key lock is provided for security on the door while still allowing easy access to the display.

The MCS-REMOTE-10.1 comes preloaded with the MCS-CONNECT program that allows you to view the unit's status, history, warnings and alarms, setpoints, and more, all in a user-friendly graphical format. Also, with the proper authorization code, changes can be made to the setpoints, sensor offsets, schedule, etc.

Kit Components

- 12VDC - Power Supply
- 120 VA outlet
- 8 Port Ethernet Switch - 10/100

Packaging

Weight40 lbs(approx)
 Box24" X 30" x 10"

Specifications

NEMA Rating – Type 1 Enclosure - IP20 Rating

Enclosure is intended for indoor use primarily to provide a degree of protection against contact with the enclosed equipment and is not protected from liquids.

Small Box - NEMA rating - Type 1

Enclosure Dimensions..... 18.25"w x 19.5"h x 8"d
 Mounting Holes..... Mounts with four pre drilled
 15/32" holes
 Input Power (Standard) 115 or 230vac ±10% 50/60Hz

Temp. Range for Enclosure & Touch Screen

Operating Temperature..... -4°F to 158°F (-20°C to 70°C)
 Operating Humidity..... 0-95% Non-Condensing
 Storage Temperature..... -4°F to 158°F (-20°C to 70°C)

Touch Screen 10.1

Dimensions..... 12.204"L x 9.055"W x 3.215"H
 Door Mount..... 10.875"L x 7.875" with cutout
 10 mount studs thru customers encl.
 HT800 Cellular Silicone Gasket
 NEMA 4 IP66 rated
 LCD Screen..... 10.1" Diagonal (Aspect Ratio 16:10)
 16.2 Million Colors
 1280 x 800 Resolution
 View Angle 85°U, 85°D, 85°L, 85°R
 5-Wire resistive touch w/Stylus pen
 White LED Backlight (Min Life 50,000 Hrs)
 Luminance Min. 400 cd/m²
 Surface Treatment..... Glare/Anti-Reflection ≤1.5%
 Hard-Coating (3H)
 Operating Temperature.....-4°F to +149°F (-20°C to +65°C)
 Operating Humidity..... 0-95% Non-Condensing
 Storage Temperature..... -13°F to +158°F (-25°C to +70°C)
 Input Power (Standard) 12 vdc Regulated Power Supply
 Minimum (Brown in)6.00 vdc
 Amp Draw (Loaded)826.0 mA
 Motherboard-Rev 4.0..... Freescale i.MX6 Dual Core 800mhz
 2Gb of 512mhz DDR3 RAM memory
 16Gb of eMMC Flash memory
 10m/100m/1G Ethernet
 1 Micro-SD Slots
 1 USB On-The-Go (OTG)
 2 USB Host 2.0
 Real Time Clock (RTC) w/ Battery
 LVDS for 15.4" LCD 5-wire touch
 3 RS485 communication ports
 (max. baud rate 115k)
 Mini PCIe Interface