



No.	Name	Note	No.	Name	Note
1	Angle valve	1/4"Flare	11	Refrigerant service valve	1/4"Flare
2	Discharge flange*	2"	12	Liquid injection connector	3/8"Flare, option
3	Solenoid valve	33%(NC)	13	Suction flange	2"
4	Solenoid valve	66%(NC)	14	Cable box	Standard
5	Liquid/oil or refrigerant injection connector	1/4"Flare, option	15	Service flange	option
6	Capillary		16	Oil drain valve	option
7	Check valve	2"	17	Discharge temp. sensor	110°C
8	Service flange		18	Economizer connector	5/8", solder
9	Oil inlet Connector	3/8"Flare	19	Safety Valve	option
10	Angle valve	1/4"Flare	20	Solenoid valve	Stepless(NO), option

* All stop valves are optional.
 * Discharge side should be connected with 1 1/2" pipe.

Dimensional Outline Drawing & Component Description
 for Stepless or Modulating-Type Capacity Control Application

Hanbell Model RC2-100BF, 140BF
 Date and Rev. 03/20/2009 A
 Drawn By B.Lai



Micro Control Systems, Inc.
 5877 Enterprise Parkway
 Fort Myers, Florida 33905
 Tel. (239) 694-0089 Fax (239) 694-0031
 E-mail: compressors@mcscontrols.com

Hanbell Precise Machinery Co., Ltd.