

Specif-



## RC2-370A Screw Compressor-R134a

ications		Displacement	CFM	60 Hz	259		
		Rated Speed	Rpm	60 Hz	3550		
		Volume Ratio	Vi		2.6 (standard other Vi available)		
	Compressor	Nominal Hp			130 Hp at 60 Hz		
		Capacity Control	%		35%,50%,75% & 100% Step Capacity Control, 50%~100% Continuous Stepless Capacity Controls		
		Lubrication			Differential Pressure Feed Lubricant		
	Туре				3 Phase, 2 Pole, Squirrel Cage, Induction Motor		
	Motor	Insulation			Class F		
		Protection			3 PTC Protection 1 per winding		
	Lubricant Charge	Gallons			4.2		
	Oil Heater	Watts			150		
	Hydrostatic Pressure test	lb/in <sup>2</sup> G			597		
	Weight	Pounds			1345		


## **Standard Compressors Accessories**

- Modulating Slide Capacity
- Weather Proof Terminal Box for outdoor applications
- 115/1/60 Control Voltage
- 115/1/60 Crankcase heater
- Horizonal Discharge Check Valve
- Discharge Service Valve (Discharge Stop Valve) with standard connection sizes and supplied with flanges and bushings
- Suction Service Valve (Suction Stop Valves) with standard connection sizes and supplied with flanges and bushings

- Oil Level Float Switch
- Suction Filter
- Oil Filter
- PSI Relief Valve
- Oil Sight Glass
- PT1000 for Reading Motor Temp
- INT69HBY supporting motor and discharge (PTC) temperature sensor protection as well as Phase Loss and Phase Reversal at Start Up Only

## **Ports**

- External Oil Cooler
- Liquid Injection (into screw chamber)
- Economizer
- Suction, Discharge & Oil Service



## Connections

Discharge Stop Valve	2 1/2"			-		
Horizonal Discharge Check Valve	2 1/2"		9			
Suction Stop Valve	4"				,4	
Economizer	7/8" solder					
Liquid Injection (chamber)	5/8" flare	Α	В	С	D	Е
Discharge Side	Copper Pipe Sizing 2 5/8"	2.36"	4.33"	1.38"	2.63"	3.03"
Suction Side	Copper Pipe Sizing 4 1/8"	2.99"	5.71"	1.97"	4.14"	4.57"

MCC & LRA Optimized for R134a								
	Hertz	Volts	Maximum Continuous Current	Y	-Δ	Part Wind Start		
				Locked Rotor Amps (Y)	Locked Rotor Amps (D)	Locked Rotor Amps (D)	Locked Rotor Amps (DD)	
	60	220	403	460	1380	868	1335	
	60	460	193	240	720	423	650	