



MCS-NITROMAG-CENT-NEMA4-SS INDUSTRIAL CONTROL PANEL



Part # **MCS-NITROMAG-CENT-NEMA4-SS***

Description

The **MCS-NITROMAG-CENT-NEMA4-SS Industrial Control Panel** is made of stainless steel for durability and longevity. A 36"H x 30"W x 12"D NEMA 4 window kit is mounted which provides a degree of protection against falling rain, splashing water and hose directed water, undamaged by formation of ice on the panel.

A left-hand swing door with 3 hinges ensures strength, while the Fast Opener Clamp Assembly provides quick, secure access no tools or keys required.

The industrial control panel consists of a MCS-NITROMAG-15.4, MCS-IO-BASE, MCS-IO-EXT, MCS-SI-BASE(2) with MCS-SI-EXT, MCS-RO-BASE with MCS-RO-EXT(1) expansion boards.

The Control Panel is supplied with a 12V and 24V power supplies.

The capacitive touchscreen interface designed to simplify user access with the MCS-NitroMag utilizing MCS-Connect to provide both graphics and service mode access to technicians. Input method: Finger, Stylus or **Glove.

Highly accurate and does not require calibration - easy to clean glass surface. Works outdoors, bright screen, water resistant, exceptional Optics - 1280x800 resolution, sharp and vibrant images.

Control panel includes the following; 20A, 16A and a 5A Single-Pole Circuit Breaker. A 5 port 10/100/1000 Mbps Ethernet Workgroup Switch Industrial rated, Red Alarm Indicator, Yellow Warning Indicator, Emergency Stop Switch with guard and 3 Position Run/Stop Selector Switch.

There is also an electrical outlet for laptop plug-in power at the panel. SHIELDWIRE-GROUNDING multi-terminal connectors are included to eliminate stray electrical current, thereby helping to reduce line noise form the sensors to the controller.

Specifications

Certification..... UL508A - E511647

NEMA Rating – Type 4 Control Panel IP66

Industrial Control Panel

Dimensions of control panel . 36"H x 30"W x 12"D
Mounting Holes..... Mounts with four pre-drilled 15/32" holes

Rated Voltage (Standard)..... 120VAC or 230VAC
Phase / Frequency 1 Phase / 60Hz
Full Load Current(approx) 40A at 120VAC or 20A at 240VAC
Short Circuit Current Rating . 10kA

Temp. Range for Control Panel & Touch Screen

LCD Screen..... 15.4" (16:10 Diagonal)
16.2 Million Colors
1280x800 Resolution
View Angle 70°U, 70°D, 70°L, 70°R
Capacitive Stylus pen
White LED Backlight (Min Life 50,000 Hrs)
Luminance Min. 350 Min. 450 Typical
Touchscreen Surface..... UV Degradation Protection
Operating Temperature..... -22°F to 176°F (-30°C to +80°C)
Operating Humidity..... 90 %RH (Non Condensing)
Storage Temperature..... -22°F to 176°F (-30°C to +80°C)

Controller

Microprocessor..... Broadcom BCM2711 Quad core
Cortex (ARMv8) 64-bit SoC @ 1.5Ghz

INPUT	MINIMUM	NOMINAL	MAXIMUM
VOLTAGE	10	12	12.5
AMPS			2

Flash Memory 16 GB EMMC
RAM 2 GB DDR3
MCS-I/O Comm Port. 1 @ 38,400 baud
RS-485 Ports..... 2 @ go up to 115200 baud rate
Ethernet..... 10Mbps/100Mbps/1Gbps
HDMI 2 HDMI 2.0 ports-Standard and Micro
WiFi..... 2.4GHz, 5.0GHz 8.02 b/g/n/ac wireless
USB 2 USB type B 2.0 ports 480Mbps signalling
Protocols..... BACnet IP, BACnet MSTP, Modbus IP, Modbus RTU Slave, Modbus RTU Master (BTL certification pending)
Real Time Clock Battery backup(Type BR2032)
Power Detection Automatic power fail reset

Power Supply - Specification

12vdc power supply.....85vac ~ 264vac
AC frequency range.....47 ~ 63Hz / 7.5A / 90W

24vdc power supply.....85vac ~ 264vac
AC frequency range.....47 ~ 63Hz / 4A / 96W

Packaging

Weight 90 lbs(approx)
Box 29" x 10" x 37"

5580 Enterprise Pkwy., Fort Myers, FL 33905
Office: 239-694-0089 • Fax: 239-694-0031 www.mcscontrols.com

* Photo shown is an example of an Industrial Control Panel; some optional equipment may be shown.

** The glove needs to have a conductive fabric or material to work with cap touchscreens.