

# MCS-T100-AVG-20

# **Description & Specifications**



Part # MCS-T100-AVG-20

# Description

The MCS-T100-AVG-20 comprised of four MCS-T100-20s in addition to a Nema 4X mounting enclosure used to read the average temperature. The Nema 4X is a durable, weatherproof, enclosure which is suited to be mounted inside or outside.

By mounting four MCS-T100-20 temperature sensors in different locations in the duct the MCS-T100-AVG-20 provides an average duct temperature. The MCS-T100-AVG-20 uses stock MCS-T100-20 sensors. Therefore, if a sensor goes bad, a replacement MCS-T100-20 sensor is the only requirement, minimizing maintenance costs. The MCS-T100-AVG-20 also has simple and easy wire instructions (see Wiring diagram right).

For a cross reference table between °F /°C, ohms and vdc at a sensor input pin (S1) of a MCS micro controller, please see the MCS-T100 specification sheet.

# **Specifications**

### **Temperature Sensor**

Standard Temperature Range ......+32°F to +158°F  $(0^{\circ}C \text{ to } +70^{\circ}C)$ Standard Temperature Accuracy...±0.36° F (±0.2°C) Extended Temperature Range.....-40°F to +248° F (-40°C to 120°C) Extended Temperature Accuracy±1.5°F (±0.8°C) Resistance Range ......2 Meg to 286 ohms Response Time (32 to 212°F)......22 sec (in liquid) Response Time (212 to 32°F)......30 sec (in liquid) Input Voltage.....5vdc


#### **Sensor Housing Specifications:**

Material......304 Stainless Steel Environmental rating......Waterproof to IP68 Testing ......10,000 freeze/thaw thermal cycles

Wire ......2 conductor 22 awg stranded Length......20' Shield......Foil shield with 25% overlap Drain.....Stranded tinned copper drain

### **Mounting Enclosure**

Dimensions.......4.7" x 4.7" x 3.5" Nema Rating......4. 4x. 12. 13 IP Rating.....IP66 Material ...... Acrylonitrile Butadiene Styrene Color......Grey Flammability Rating.....UL94HB



Revision - 2018-05-30